

Electrical Assembly Specification

ELECTRICAL RATINGS - T RATINGS - AMBIENT TEMPERATURES			
SWITCH CONFIGURATION	ELECTRICAL RATING	MAX AMBIENT OPERATING TEMP °C (°F)	TEMPERATURE CODE (MAX SURFACE TEMP)
FORM “C” SPDT 057-0770	11 AMP OR ¼ HP AT 125 OR 250 VAC	75 (167)	T5
		60 (140)	T6
	5 AMP AT 125 OR 250 VAC; 5 AMP RES, 3 AMP IND AT 28 VDC; 0.5 AMP RES AT 125 VDC	70 (158)	
FORM “CC” DPDT 057-0771	11 AMP OR ¼ HP AT 125 OR 250 VAC	65 (149)	T4A
		45 (113)	T6
	5 AMP AT 125 OR 250 VAC; 5 AMP RES, 3 AMP IND AT 28 VDC; 0.5 AMP RES AT 125 VDC	70 (158)	
M OPTION FORM “C” & “CC” 057-0772 (SPDT) 057-0773 (DPDT)	1 AMP AT 125 VAC		

All Standard Enclosure 6 - Pressure and Temperature Switches carry one of the electrical assemblies listed in the Table above.

These assemblies carry one or all of the following agency listings.

Underwriters Laboratories, Inc., File number E56677

CSA International, File number LR34146

Factory Mutual, File number J.1.IR5A9.AE

SIRA, 02ATEX1087X